


FORM PTO-1390 (Modified) (REV 11-2000)		U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE		ATTORNEY'S DOCKET NUMBER PD990069	
TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371				U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR <div style="font-size: 1.5em; font-weight: bold; text-align: center;">10/089507</div>	
INTERNATIONAL APPLICATION NO. PCT/EP00/07395		INTERNATIONAL FILING DATE 31 JULY 2000 (31.07.00)		PRIORITY DATE CLAIMED 30 SEPTEMBER 1999 (30.09.99)	
TITLE OF INVENTION <div style="text-align: center; font-weight: bold; margin-top: 10px;"> METHOD FOR POWER LEVEL CONTROL OF A DISPLAY DEVICE AND APPARATUS FOR CARRYING OUT THE METHOD </div>					
APPLICANT(S) FOR DO/EO/US <div style="text-align: center; font-weight: bold; margin-top: 10px;"> Carlos Correa, Sebastien Weitbruch and Rainer Zwing </div>					
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:					
<ol style="list-style-type: none"> 1. <input checked="" type="checkbox"/> This is a FIRST submission of items concerning a filing under 35 U.S.C. 371. 2. <input type="checkbox"/> This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371. 3. <input checked="" type="checkbox"/> This is an express request to begin national examination procedures (35 U.S.C. 371(f)). The submission must include items (5), (6), (9) and (24) indicated below. 4. <input type="checkbox"/> The US has been elected by the expiration of 19 months from the priority date (Article 31). 5. <input checked="" type="checkbox"/> A copy of the International Application as filed (35 U.S.C. 371 (c) (2)) <ol style="list-style-type: none"> a. <input type="checkbox"/> is attached hereto (required only if not communicated by the International Bureau). b. <input checked="" type="checkbox"/> has been communicated by the International Bureau. c. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US). 6. <input checked="" type="checkbox"/> An English language translation of the International Application as filed (35 U.S.C. 371(c)(2)). <ol style="list-style-type: none"> a. <input checked="" type="checkbox"/> is attached hereto. b. <input type="checkbox"/> has been previously submitted under 35 U.S.C. 154(d)(4). 7. <input checked="" type="checkbox"/> Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371 (c)(3)) <ol style="list-style-type: none"> a. <input type="checkbox"/> are attached hereto (required only if not communicated by the International Bureau). b. <input type="checkbox"/> have been communicated by the International Bureau. c. <input type="checkbox"/> have not been made; however, the time limit for making such amendments has NOT expired. d. <input checked="" type="checkbox"/> have not been made and will not be made. 8. <input type="checkbox"/> An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)). 9. <input checked="" type="checkbox"/> An oath or declaration of the inventor(s) (35 U.S.C. 371 (c)(4)). 10. <input checked="" type="checkbox"/> An English language translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371 (c)(5)). 11. <input checked="" type="checkbox"/> A copy of the International Preliminary Examination Report (PCT/IPEA/409). 12. <input checked="" type="checkbox"/> A copy of the International Search Report (PCT/ISA/210). 					
Items 13 to 20 below concern document(s) or information included:					
<ol style="list-style-type: none"> 13. <input checked="" type="checkbox"/> An Information Disclosure Statement under 37 CFR 1.97 and 1.98. 14. <input checked="" type="checkbox"/> An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included. 15. <input checked="" type="checkbox"/> A FIRST preliminary amendment. 16. <input type="checkbox"/> A SECOND or SUBSEQUENT preliminary amendment. 17. <input type="checkbox"/> A substitute specification. 18. <input checked="" type="checkbox"/> A change of power of attorney and/or address letter. 19. <input type="checkbox"/> A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821 - 1.825. 20. <input type="checkbox"/> A second copy of the published international application under 35 U.S.C. 154(d)(4). 21. <input type="checkbox"/> A second copy of the English language translation of the international application under 35 U.S.C. 154(d)(4). 22. <input checked="" type="checkbox"/> Certificate of Mailing by Express Mail 23. <input checked="" type="checkbox"/> Other items or information: 					
Return Postcard Receipt					
EXPRESS MAIL NO: EL 722193664 US			DATE OF DEPOSIT: MARCH 28, 2002		

U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR 1.101) 70/089507		INTERNATIONAL APPLICATION NO. PCT/EP00/07395		ATTORNEY'S DOCKET NUMBER PD990069																					
24. The following fees are submitted: BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)) : <input type="checkbox"/> Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO \$1040.00 <input checked="" type="checkbox"/> International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO \$890.00 <input type="checkbox"/> International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO \$740.00 <input type="checkbox"/> International preliminary examination fee (37 CFR 1.482) paid to USPTO but all claims did not satisfy provisions of PCT Article 33(1)-(4) \$710.00 <input type="checkbox"/> International preliminary examination fee (37 CFR 1.482) paid to USPTO and all claims satisfied provisions of PCT Article 33(1)-(4) \$100.00 ENTER APPROPRIATE BASIC FEE AMOUNT =				CALCULATIONS PTO USE ONLY																					
Surcharge of \$130.00 for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492 (e)).				\$890.00																					
<table border="1"><thead><tr><th>CLAIMS</th><th>NUMBER FILED</th><th>NUMBER EXTRA</th><th>RATE</th></tr></thead><tbody><tr><td>Total claims</td><td>8 - 20 =</td><td>0</td><td>x \$18.00</td></tr><tr><td>Independent claims</td><td>1 - 3 =</td><td>0</td><td>x \$84.00</td></tr><tr><td colspan="3">Multiple Dependent Claims (check if applicable).</td><td><input type="checkbox"/></td></tr><tr><td colspan="3">TOTAL OF ABOVE CALCULATIONS</td><td>=</td></tr></tbody></table>				CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE	Total claims	8 - 20 =	0	x \$18.00	Independent claims	1 - 3 =	0	x \$84.00	Multiple Dependent Claims (check if applicable).			<input type="checkbox"/>	TOTAL OF ABOVE CALCULATIONS			=	\$0.00	
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE																						
Total claims	8 - 20 =	0	x \$18.00																						
Independent claims	1 - 3 =	0	x \$84.00																						
Multiple Dependent Claims (check if applicable).			<input type="checkbox"/>																						
TOTAL OF ABOVE CALCULATIONS			=																						
<input type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27. The fees indicated above are reduced by 1/2.				\$0.00																					
SUBTOTAL				= \$890.00																					
Processing fee of \$130.00 for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492 (f)).				\$0.00																					
TOTAL NATIONAL FEE				= \$890.00																					
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31) (check if applicable).			<input checked="" type="checkbox"/>	\$40.00																					
TOTAL FEES ENCLOSED				= \$930.00																					
				Amount to be: refunded \$																					
				charged \$																					
a. <input type="checkbox"/> A check in the amount of _____ to cover the above fees is enclosed. b. <input checked="" type="checkbox"/> Please charge my Deposit Account No. 07-0832 in the amount of \$930.00 to cover the above fees. A duplicate copy of this sheet is enclosed. c. <input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 07-0832 A duplicate copy of this sheet is enclosed. d. <input type="checkbox"/> Fees are to be charged to a credit card. WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.																									
NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.																									
SEND ALL CORRESPONDENCE TO: Mr. Joseph S. Tripoli THOMSON multimedia Licensing Inc. Patent Department P. O. Box 5312 Princeton, New Jersey 08540																									
<div> SIGNATURE JOSEPH S. TRIPOLI NAME 26,040 REGISTRATION NUMBER March 28, 2002 DATE</div>																									

EXPRESS MAIL LABEL NO. EL 722193664 US

PD990069

10/089507
JC13 Rec'd PCT/PTO 28 MAR 2002

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant : Carlos Correa et al.

Filed : July 31, 2000 - PCT National Phase of PCT/EP00/07395

For : METHOD FOR POWER LEVEL CONTROL OF A DISPLAY
DEVICE AND APPARATUS FOR CARRYING OUT THE METHOD

PRELIMINARY AMENDMENT

Hon. Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Sir:

In the US national phase application of PCT/EP00/07395 please
enter the following amendments.

IN THE SPECIFICATION:

Please amend the specification as follows:

Page 1, after the title, insert the following:

--This application claims the benefit under 35 U.S.C. § 365 of
International Application PCT/EP00/07395, filed July 31, 2000, which claims
the benefit of European Application No. 99250347.4, filed September 30,
1999.--

**IN THE CLAIMS (As Annexed to the International Preliminary Examination
Report:**

Please amend the claims as follows. This is the clean version.
Attached is the marked up version of these claims.

1. (Amended) Method for power level control in a display device having
a plurality of display elements corresponding to the pixels of a
picture, wherein a power level mode selection process is used for
increasing the peak white enhancement factor of the display, in

which the power value of a video picture is measured and a corresponding power level mode is selected for controlling the display contrast, wherein a picture is divided in a number of blocks, wherein in each block the video levels or values derived from the video levels of the colour components of the pixels are summed up in order to determine the local power values for the picture, wherein a local temperature estimation is performed for the corresponding blocks of the display based on said local power values and the previously estimated local temperature values, wherein in the estimated local temperature values the maximum local temperature in the display is selected, wherein a further step of maximum power level limit determination is performed based on the maximum local temperature, and wherein the power level limit is used to restrict the range of selectable power level modes in the power level mode selection process to power level modes having a power level below or equal to said power level limit.

2. (Amended) Method according to claim 1, wherein for local temperature estimation of a block, the power dissipation not only of the local block but also of a number of neighboring blocks is taken into account.
3. (Amended) Method according to claim 1, wherein the maximum local temperature determination for the display is performed once in a number of video frames.
4. Method according to claim 3, wherein the steps of local power value determination and local temperature estimation are performed only for one or more selected blocks of the whole picture within a frame period.

EXPRESS MAIL LABEL NO. EL 722193664 US

PD990069

5. (Amended) Method according to claim 3, wherein a picture is divided in 40 blocks and the maximum local temperature determination is performed once within 40 frame periods.
6. (Amended) Method according to claim 1, wherein the switching between maximum allowed power level limits corresponding to the determined maximum local temperature is controlled with a power level mode against picture power curve that falls if the picture power is increasing and that rises if the picture power is decreasing, and with a delay between falling and rising, respectively rising and falling if the change direction of the picture power value changes.
7. (Amended) Apparatus for carrying out the method according to claim 1, the apparatus having included a power level determination and selection unit, and a local power determination unit, wherein for a picture that is divided in a number of blocks, per block the video levels or values derived from the video levels of the colour components of the pixels are summed up in order to determine the local power values for the picture, wherein, said apparatus further includes a local temperature estimator, that performs a local temperature estimation per block of the display based on said local power values and the previously estimated local temperature values, a maximum local temperature selector that selects the maximum local temperature from the estimated local temperatures, a maximum power level limit selector that assigns a maximum power level limit to the selected maximum local temperature, and a power level limiter, wherein the power level limiter restricts the range of selectable power level modes in the power level mode selector to power level modes having a power level below or equal to said selected maximum power level limit.

EXPRESS MAIL LABEL NO. EL 722193664 US

PD990069

8. Apparatus according to claim 7, wherein it is integrated in a plasma display device.

IN THE ABSTRACT:

Please add the attached Abstract.

REMARKS


The specification has been amended to include a reference to the priority application.

The above amendments to the claims have been made to eliminate reference indicia and to meet the requirements of the USPTO.

To meet the requirements of the United States, the Abstract has been added.

No fee is believed to have been incurred by virtue of this amendment. However, if a fee is incurred on the basis of this amendment, please charge such fee against deposit account 07-0832.

Respectfully submitted,
Carlos Correa et al.


Joseph S. Tripoli
Registration No. 26,040
609/734-9443

Enclosures

THOMSON multimedia Licensing Inc.
Patent Operation
PO Box 5312
Princeton, NJ 08543-5312

Date: March 28, 2002

Marked Up Claims

1. (Amended) Method for power level control in a display device having a plurality of display elements corresponding to the pixels of a picture,
5 wherein a power level mode selection process is used for increasing the peak white enhancement factor of the display, in which the power value of a video picture is measured and a corresponding power level mode is selected for controlling the display contrast, wherein a picture is divided in a number of blocks $[(S_{11}-S_{58})]$, wherein in each block $[(S_{11}-S_{58})]$ the video
10 levels or values derived from the video levels of the colour components of the pixels are summed up in order to determine the local power values $[(LP)]$ for the picture, **[characterised in that]** wherein a local temperature estimation is performed for the corresponding blocks of the display based on said local power values $[(LP)]$ and the previously estimated local
15 temperature values, wherein in the estimated local temperature values the maximum local temperature $[(MT)]$ in the display is selected, wherein a further step of maximum power level limit $[(PLM)]$ determination is performed based on the maximum local temperature $[(MT)]$, and wherein the power level limit $[(PLM)]$ is used to restrict the range of selectable
20 power level modes in the power level mode selection process to power level modes having a power level below or equal to said power level limit $[(PLM)]$.
2. (Amended) Method according to claim 1, wherein for local temperature
25 estimation of a block $[(S_{11}-S_{58})]$, the power dissipation not only of the local block $[(S_{11}-S_{58})]$ but also of a number of [neighbouring] neighboring blocks $[(S_{11}-S_{58})]$ is taken into account.
3. (Amended) Method according to claim 1 [or 2], wherein the maximum local
30 temperature determination for the display is performed once in a number of video frames.

4. Method according to claim 3, wherein the steps of local power value determination and local temperature estimation are performed only for one or more selected blocks of the whole picture within a frame period.

5 5. (Amended) Method according to claim 3 [or 4], wherein a picture is divided in 40 blocks and the maximum local temperature determination is performed once within 40 frame periods.

10 6. (Amended) Method according to [one of claims 1 to 5] claim 1, wherein the switching between maximum allowed power level limits corresponding to the determined maximum local temperature is controlled with a power level mode against picture power curve that falls if the picture power is increasing and that rises if the picture power is decreasing, and with a delay between falling and rising, respectively rising and falling if the change
15 direction of the picture power value changes.

20 7. (Amended) Apparatus for carrying out the method according to [one of the previous claims] claim 1, the apparatus having included a power level determination and selection unit [(16, 17)], and a local power determination unit [(18)], wherein for a picture that is divided in a number of blocks [(S₁₁-S₅₈)], per block [(S₁₁-S₅₈)] the video levels or values derived from the video levels of the colour components of the pixels are summed up in order to determine the local power values [(LP)] for the picture, [**characterised in that**] wherein, said apparatus further includes a local temperature estimator
25 [(19)], that performs a local temperature estimation per block of the display based on said local power values [(LP)] and the previously estimated local temperature values, a maximum local temperature selector [(20)] that selects the maximum local temperature from the estimated local temperatures, a maximum power level limit selector [(21)] that assigns a
30 maximum power level limit to the selected maximum local temperature, and a power level limiter [(22)], wherein the power level limiter [(22)] restricts the range of selectable power level modes in the power level mode selector

[(21)] to power level modes having a power level below or equal to said selected maximum power level limit [(PLM)].

8. Apparatus according to claim 7, wherein it is integrated in a plasma display device.

ABSTRACT

Plasma Display Panels are becoming more and more interesting for TV technology. One important criterion for picture quality is the Peak White Enhancement Factor PWEF. In a previous patent application a method for power level control in a display with which the PWEF can be increased has been proposed. With an increased PWEF the problem of local overheating of plasma cells may occur. This invention proposes a protection circuit, which deals with this problem. For protecting the plasma display against local overheating, there is provided a method, which performs the steps of local power value determination, local temperature estimation, maximum local temperature determination and maximum power level limit determination. The power level limit influences the power level control process in the display device so that local overheating is avoided and the highest possible PWEF can be used. The invention also concerns a corresponding apparatus for carrying out the proposed method.

5/pvt/-1-

Method for power level control of a display device and apparatus for carrying out the method

5 The invention relates to a method for power level control of a display device and an apparatus for carrying out the method.

10 More specifically the invention is closely related to a kind of video processing for improving the picture quality of pictures which are displayed on displays like plasma display panels (PDP), and all kind of displays based on the principle of duty cycle modulation (pulse width modulation) of light emission / reflection / transmission. Specific claim is laid on the aspect of panel temperature estimation for
15 power level control.

Background

For image quality, peak white is of paramount importance. The Peak White Enhancement Factor (PWEF) can be defined as
20 the ratio between the peak white luminance, to the luminance of a homogeneous white field, usually referred to as the full white level. CRT based displays have PWEFs of up to 5, first generation of PDPs were characterised by having a peak white to maximum average luminance ratio of about 2. This is
25 far worse than what is achieved in old CRT technology.

A Plasma Display Panel (PDP) utilizes a matrix array of discharge cells, which could only be "ON" or "OFF". Also unlike a CRT or LCD in which grey levels are expressed by analogue
30 control of the light emission, a PDP controls the grey level by modulating the number of light pulses per frame (sustain pulses). The eye will integrate this time-modulation over a period corresponding to the eye time response.

35 More sustain pulses correspond to higher peak luminance values. More sustain pulses correspond also to a higher power

-2-

that flows in the PDP. The PDP control can generate more or less sustain pulses as a function of average picture power, i.e., it switches between modes with different power levels. In this document, the Power Level of a given mode is defined
5 as the number of sustain discharges activated for a region of 100 ire video. The available range of power level modes is regarded as approximately equal to the PWEF.

A previous European patent application of the applicant with
10 application number 99101977.9 reports a technique that increases the PWEF of a PDP by increasing the number of available power level modes, in number and in range, and by introducing an hysteresis circuit in the luminance level selection control. This technique allows achieving PWEF values
15 up to 5.

PDPs have a large surface. A PWEF of 5, although pleasant to the image quality, has the disadvantage that it may concentrate, under certain circumstances, for a long time, the
20 power dissipation on a small surface of the panel. If this situation is prolonged for a long time, which may occur in case of still video, local overheating of the panel may assume unacceptable values.

25 It has been proposed in WO 99/30309 to provide a panel temperature detector beside an average picture level detector and a picture peak level detector in a PDP for the purpose of power level control.

30 Invention

The present invention has the object to further improve the power level control of displays, like PDPs. This object is achieved with the measures of claim 1. According to the invention a local temperature estimator is used instead of a
35 simple temperature detector for power level control.

-3-

This has the advantage, that also in case of still pictures, in which only small areas have high luminance values, the panel can be reliably protected against local thermal overheating by switching over to lower power level modes.

5

This proposal can be used in combination with any peak white enhancement circuit providing a large PWEF factor, not only for PDPs.

10 In other words, one main idea behind this invention is to try to build a model that describes local overheating of a panel as a function of the displayed video picture, and to use that information to control the operation of the peak white enhancement loop.

15

The invention also concerns an advantageous apparatus for carrying out the method according to the invention. This apparatus contains practically speaking a thermal protection circuit for displays having a large PWEF, and comprises the
20 following components:

1. A local power level determination unit.

2. A local temperature estimation unit.

25

3. A maximum local temperature determination unit.

4. A selector of the maximum allowed power level mode, as a function of the estimated maximum local temperature value.

30 This function should include hysteresis, in order to prevent the occurrence of perceivable luminance oscillations.

5. A limiter of the current power level value, to the selected maximum allowed power level. This limiter actually
35 performs the protection function because it determines the sub-field organisation and sustain pulse generation which

corresponds to the determination of the flow of energy into the PDP.

Advantageous additional embodiments to the claimed power level control method and apparatus are apparent from the dependent claims.

Drawings

Exemplary embodiments of the invention are illustrated in the drawings and are explained in more detail in the following description.

In the figures:

- Fig. 1 shows an illustration for explaining the sub-field concept of a PDP;
- Fig. 2 shows two different sub-field organisations to illustrate the concept of switching between different power level modes for peak white enhancement;
- Fig. 3 shows a block diagram of a plasma display apparatus inclusive power level control apparatus such as known from EP 99101977.9;
- Fig. 4 shows a hysteresis curve used for power level selection in the apparatus shown in Fig. 1;
- Fig. 5 shows a block diagram of a plasma display apparatus inclusive power level control apparatus according to the invention;
- Fig. 6 shows a first partition of the display panel into blocks of pixels for the local temperature estimation;
- Fig. 7 shows a second partition of the display panel into blocks of pixels for the local temperature estimation with overlapping of blocks partly allowed;
- Fig. 8 shows a third partition of the display panel into blocks of pixels for the local temperature estimation;

tion with overlapping of blocks partly allowed
and;

Fig. 9 shows a hysteresis curve used for maximum power
level limit selection.

5

Exemplary Embodiments

The principles behind this invention are now explained by
means of an example. It is strongly noted that values in an
10 actual implementation may differ from those here shown, in
particular the number and weight of the used sub-fields and
the number of actual sustain pulses.

In the field of video processing is an 8-bit representation
15 of a luminance level very common. In this case each video
level will be represented by a combination of the following
8 bits:

$2^0 = 1$, $2^1 = 2$, $2^2 = 4$, $2^3 = 8$, $2^4 = 16$, $2^5 = 32$, $2^6 = 64$,
20 $2^7 = 128$

To realise such a coding scheme with the PDP technology, the
frame period will be divided in 8 sub-periods which are also
very often referred to sub-fields, each one corresponding to
25 one of the 8 bits. The duration of the light emission for
the bit $2^1 = 2$ is the double of that for the bit $2^0 = 1$ etc.
With a combination of these 8 sub-periods, we are able to
build 256 different grey levels. E.g. the grey level 92 will
thus have the corresponding digital code word %1011100. It
30 should be appreciated, that in PDP technology the sub-fields
consist each of a corresponding number of small pulses with
equal amplitude and equal duration. Without motion, the eye
of the observer will integrate over about a frame period all
the sub-periods and will have the impression of the right
35 grey level. The above-mentioned sub-field organisation is
shown in Fig. 1. Note that Fig. 1 is simplified in that re-

spect that the time periods for addressing the plasma cells and for erasing the plasma cells after addressing (scanning) and sustaining are not explicitly shown. However, they are present for each sub-field in plasma display technology which is well known to the skilled man in this field. These time periods are mandatory and can be constant for each sub-field.

When all sub-fields are activated, the lighting phase has a relative duration of 255 relative time units. The value of 255 has been selected in order to be able to continue using the above-mentioned 8-bit representation of the luminance level or RGB data which is being used for PDPs. The second sub-field in Fig. 1 has e.g. a duration of 2 relative time units. In the field of PDP technology, the relative duration of a sub-field is often referred to the 'weight' of a sub-field, the expression will also be used hereinafter.

An efficient peak white enhancement control circuit requires a high number of discrete power level modes for mapping the 8 bit words of video signal level (RGB-, YUV-signals) to respective sub-field code words. Switching is done between the different power level modes as e.g. described in the European Patent Application 99101977.9 of the applicant. For the disclosure of the invention it is therefore also referred to the content of this application.

In Fig. 2 it is briefly shown how the principle of dynamic sub-field organisation works. Two modes with different power levels are shown.

In the first mode the sub-field organisation is composed of 11 sub-fields SF' and in the second mode it is composed of 9 sub-fields. Each sub-field SF consists of an addressing period sc (scan period) where each plasma cell is charged or not charged determined by the code word for each pixel, a

-7-

sustain period su where the pre-charged plasma cells are activated for light emission and an erase period er, where the plasma cells are discharged. In the 9 sub-field case, less time is required for addressing (scan), and therefore more time is available for sustain pulses (the area in black is larger). The erase and scan time of a sub-field is independent of the corresponding sub-field weight. It can be seen from the figure, that the sub-field position and the sub-field weight is different for the two shown cases. For instance in the first shown case, the weight of the seventh sub-field is 32, and in the second case, the weight of the seventh sub-field is 64. The depicted relative time duration for addressing, erasing and sustain times are only exemplary and may be different in certain implementations. Also it's not mandatory, that the sub-fields with low weights are positioned at the beginning and the sub-fields with higher weights are positioned at the end of the field/frame period.

Supposed is a PDP device with a PWEF of 5. Video is coded from 0 to 255. Power level control generates a maximum of 5×255 sustain pulses (peak white) and a minimum of 255 pulses (full white), for 100 ire, in the mode with lower power level.

A solution was described using 4 different main modes:

Mode 1: 12 sub-fields (2×255 sustain pulses):

1 - 2 - 4 - 8 - 16 - 32 - 32 - 32 - 32 - 32 - 32 - 32

Mode 2: 11 sub-fields (3×255 sustain pulses):

1 - 2 - 4 - 8 - 16 - 32 - 32 - 40 - 40 - 40 - 40

Mode 3: 10 sub-fields (4×255 sustain pulses):

1 - 2 - 4 - 8 - 16 - 32 - 48 - 48 - 48 - 48

35

Mode 4: 9 sub-fields (5×255 sustain pulses):

•

As it should be expected, when picture power level increases, modes are selected with decreasing power levels. There is an hysteresis loop in the control function. When picture average power is increasing, modes with power levels on the top line are chosen. When picture power is decreasing, modes with power levels on the bottom line are chosen. Points between the two lines can be chosen when the picture average power growth direction is modified. With this power level control method the power supply of a PDP is protected. An overload of the power supply in case of pictures with high average picture power values is avoided. On the other hand in case of low average picture power values more sustain pulses are produced and the power supply can provide the required current without being overloaded.

Fig. 5 depicts a peak white enhancement circuit with a thermal protection circuit for the PDP, which is the core of this invention. The blocks drawn in bold correspond to the blocks that constitute the protection circuit.

This protection circuit is based on a circuit described in another European patent application of the applicant with application number 99112906.5.

At first, the local power measurement block is described. The main idea is to divide the total display surface in many blocks S_{ij} , and then to integrate (add) the input video levels for all pixels in the block, which means for each pixel the video levels of the 3 colour components are added, thus obtaining a value P_{ij} :

$$P_{ij} = \sum (k \in S_{ij}) (R_k + G_k + B_k)$$

where k denotes all pixels belonging to S_{ij} .

5

$$P_{ij} = \sum (k \in S_{ij}) (R_k^3 + G_k^3 + B_k^3)$$

10

20

25

30

25

The temperature of a given block is, in a first approximation, equal to the previous temperature estimation $T(i,j)_{t-1}$, plus the power being dissipated $a \cdot P(i,j)_t$ in the block in the current frame period, minus a dissipation term D corresponding to the heat being given to the environment per frame time:

$$T(i,j)_t = T(i,j)_{t-1} + a \cdot P(i,j)_t - D$$

This model can be improved by making the assumption that the heat dissipation is proportional to the actual temperature:

$$T(i,j)_t = T(i,j)_{t-1} + a \cdot P(i,j)_t - b \cdot T(i,j)_{t-1}$$

Furthermore, thermal dispersion to the near-by blocks can also be considered:

$$\begin{aligned} T(i,j)_t = & T(i,j)_{t-1} + a \cdot P(i,j)_t - b \cdot T(i,j)_{t-1} - \\ & c \cdot [T(i-1,j)_{t-1} - T(i,j)_{t-1}] - \\ & c \cdot [T(i+1,j)_{t-1} - T(i,j)_{t-1}] - \\ & c \cdot [T(i,j-1)_{t-1} - T(i,j)_{t-1}] - \\ & c \cdot [T(i,j+1)_{t-1} - T(i,j)_{t-1}] \end{aligned}$$

The newly added terms can be either negative (if the near-by blocks are cooler) or positive (if the near-by blocks are hotter). Finally, for a last further refinement, diagonal thermal dispersion might also be considered by adding 4 further terms, but the complexity of the shown model should be enough for all practical purposes.

The above model also deals with the border effect. Blocks at the border, or at the corners will have less dissipation possibilities, due to the fact that they have less near-by blocks. They may overheat quicker, for the same power being

dissipated, but this should be correctly detected by the last here presented model.

Next, the maximum local temperature determination in block 5 20 is explained. In principle to find the maximum local temperature MT, it is required to evaluate, in the current example, the 40 P_{ij} values ($40 = 5 \text{ rows} * 8 \text{ columns}$) in block 18 and the corresponding 40 T_{ij} values in block 19, and then finding the maximum in block 20. This requires quite a number of operations per frame, with a large number of video 10 integrators working in parallel.

Thermal heating is however a very slow process, and so the following approximation might be used:

15

1. For every frame the dissipation on a single picture block is calculated, i.e., power dissipation in every block is evaluated only once for every group of 40 frames (in this example).

20

2. For the selected picture block the local temperature is computed in block 19 using the following expression:

$$T(i,j)_t = T(i,j)_{t-40} + a \cdot P(i,j)_t - b \cdot T(i,j)_{t-40} -$$

$$25 \quad c \cdot [T(i-1,j)_{t-40} - T(i,j)_{t-40}] -$$

$$c \cdot [T(i+1,j)_{t-40} - T(i,j)_{t-40}] -$$

$$c \cdot [T(i,j-1)_{t-40} - T(i,j)_{t-40}] -$$

$$c \cdot [T(i,j+1)_{t-40} - T(i,j)_{t-40}]$$

30 Here, the index $t-40$ means that the corresponding temperature value is an old value being calculated before, at maximum 40 frames before. Of course, the power dissipation term $a \cdot P(i,j)_t$ ignores all the power dissipations coming from the 40 frames between two temperature estimations for the same 35 block and this is a drawback of the model. However it has been proofed that in practice this error is for TV pictures

•

5

10

15

30

35

-15-

It is also possible to have dynamic peak white control without having a protection circuit. Picture quality will however not be the same, because the dynamic peak white control
 5 will use a restricted range for the PWEF, in order to avoid unacceptable local thermal overheating.

Claims

1. Method for power level control in a display device
 having a plurality of display elements corresponding to
 5 the pixels of a picture, wherein a power level mode
 selection process is used for increasing the peak white
 enhancement factor of the display, in which the power
 value of a video picture is measured and a corresponding
 power level mode is selected for controlling the display
 10 contrast, wherein a picture is divided in a number of
 blocks (S_{11} - S_{58}), wherein in each block (S_{11} - S_{58}) the
 video levels or values derived from the video levels of
 the colour components of the pixels are summed up in
 order to determine the local power values (LP) for the
 15 picture, **characterised in that** a local temperature
 estimation is performed for the corresponding blocks of
 the display based on said local power values (LP) and
 the previously estimated local temperature values,
 wherein in the estimated local temperature values the
 20 maximum local temperature (MT) in the display is
 selected, wherein a further step of maximum power level
 limit (PLM) determination is performed based on the
 maximum local temperature (MT), and wherein the power
 level limit (PLM) is used to restrict the range of
 25 selectable power level modes in the power level mode
 selection process to power level modes having a power
 level below or equal to said power level limit (PLM).

2. Method according to claim 1, wherein for local
 30 temperature estimation of a block (S_{11} - S_{58}), the power
 dissipation not only of the local block (S_{11} - S_{58}) but
 also of a number of neighbouring blocks (S_{11} - S_{58}) is
 taken into account.

3. Method according to claim 1 or 2, wherein the maximum local temperature determination for the display is performed once in a number of video frames.
- 5 4. Method according to claim 3, wherein the steps of local power value determination and local temperature estimation are performed only for one or more selected blocks of the whole picture within a frame period.
- 10 5. Method according to claim 3 or 4, wherein a picture is divided in 40 blocks and the maximum local temperature determination is performed once within 40 frame periods.
- 15 6. Method according to one of claims 1 to 5, wherein the switching between maximum allowed power level limits corresponding to the determined maximum local temperature is controlled with a power level mode against picture power curve that falls if the picture power is increasing and that rises if the picture power is decreasing, and with a delay between falling and rising, respectively rising and falling if the change direction of the picture power value changes.
- 20 7. Apparatus for carrying out the method according to one of the previous claims, the apparatus having included a power level determination and selection unit (16, 17), and a local power determination unit (18), wherein for a picture that is divided in a number of blocks (S_{11} - S_{58}), per block (S_{11} - S_{58}) the video levels or values derived from the video levels of the colour components of the pixels are summed up in order to determine the local power values (LP) for the picture, **characterised in that**, said apparatus further includes a local temperature estimator (19), that performs a local temperature estimation per block of the display based on
- 25
- 30
- 35

said local power values (LP) and the previously
estimated local temperature values, a maximum local
temperature selector (20) that selects the maximum local
temperature from the estimated local temperatures, a
5 maximum power level limit selector (21) that assigns a
maximum power level limit to the selected maximum local
temperature, and a power level limiter (22), wherein the
power level limiter (22) restricts the range of
selectable power level modes in the power level mode
10 selector (21) to power level modes having a power level
below or equal to said selected maximum power level
limit (PLM).

8. Apparatus according to claim 7, wherein it is integrated
15 in a plasma display device.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
5 April 2001 (05.04.2001)

PCT

(10) International Publication Number
WO 01/24150 A1

(51) International Patent Classification⁷: **G09G 3/28**

[FR/DE]: Chabeuilstrasse 7, D-78087 Mönchweiler (DE).
ZWING, Rainer [DE/DE]; Bozener Strasse 2, D-78052
Villingen-Schwenningen (DE).

(21) International Application Number: **PCT/EP00/07395**

(22) International Filing Date: **31 July 2000 (31.07.2000)**

(74) Agent: **SCHÄFERJOHANN, Volker**; Deutsche
Thomson-Brandt GmbH, European Patent Operations,
Karl-Wiechert-Allee 74, D-30625 Hannover (DE).

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data:
99250347.4 30 September 1999 (30.09.1999) **EP**

(81) Designated States (*national*): AE, AG, AL, AU, BA, BB,
BG, BR, CA, CN, CR, CU, CZ, DM, DZ, EE, GD, GE, HR,
HU, ID, IL, IN, IS, JP, KP, KR, LC, LK, LR, LV, MA, MG,
MK, MN, MX, NO, NZ, PL, RO, SG, SI, SK, TR, TT, UA,
US, UZ, VN, YU, ZA.

(71) Applicant (*for all designated States except US*):
DEUTSCHE THOMSON-BRANDT GMBH [DE/DE];
Hermann-Schwer-Strasse 3, D-78048 Villingen-Schwen-
ningen (DE).

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG,
CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **CORREA, Car-
los** [PT/DE]; Lichtenberger Weg 4, D-78056 Villin-
gen-Schwenningen (DE). **WEITBRUCH, Sébastien**

Published:
— With international search report.

[Continued on next page]

(54) Title: METHOD FOR POWER LEVEL CONTROL OF A DISPLAY DEVICE AND APPARATUS FOR CARRYING OUT THE METHOD

S ₁₁	S ₁₂	S ₁₃	S ₁₄	S ₁₅	S ₁₆	S ₁₇	S ₁₈
S ₂₁	S ₂₂	S ₂₃	S ₂₄	S ₂₅	S ₂₆	S ₂₇	S ₂₈
S ₃₁	S ₃₂	S ₃₃	S ₃₄	S ₃₅	S ₃₆	S ₃₇	S ₃₈
S ₄₁	S ₄₂	S ₄₃	S ₄₄	S ₄₅	S ₄₆	S ₄₇	S ₄₈
S ₅₁	S ₅₂	S ₅₃	S ₅₄	S ₅₅	S ₅₆	S ₅₇	S ₅₈

(57) Abstract: Plasma Display Panels (PDP) are becoming more and more interesting for TV technology. One important criterion for picture quality is the Peak White Enhancement Factor PWEF. In a previous patent application a method for power level control in a display with which the PWEF can be increased has been proposed. With an increased PWEF the problem of local overheating of plasma cells may occur. This invention proposes a protection circuit, which deals with this problem. For protecting the plasma display against local overheating, there is provided a method, which performs the steps of local power value determination (18), local temperature estimation (19), maximum local temperature determination (20) and maximum power level limit determination (21). The power level limit influences the power level control process (22) in the display device so that local overheating is avoided and the highest possible PWEF can be used. The invention also concerns a corresponding apparatus for carrying out the proposed method.

WO 01/24150 A1

WO 01/24150 A1



— Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

PD990069

1/5




Fig. 1




Fig. 2

PD 990069




Fig.3




Fig.4

PD 990069




Fig.5




Fig.6

PD990069

4/5

S_{11}	S_{12}	S_{13}	S_{14}	S_{15}	S_{16}	S_{17}	S_{18}
S_{21}	S_{22}	S_{23}	S_{24}	S_{25}	S_{26}	S_{27}	S_{28}
S_{31}	S_{32}	S_{33}	S_{34}	S_{35}	S_{36}	S_{37}	S_{38}
S_{41}	S_{42}	S_{43}	S_{44}	S_{45}	S_{46}	S_{47}	S_{48}
S_{51}	S_{52}	S_{53}	S_{54}	S_{55}	S_{56}	S_{57}	S_{58}

Fig. 7





Fig. 8

PD990069

5/5



DECLARATION FOR UNITED STATES PATENT APPLICATION,
POWER OF ATTORNEY, DESIGNATION OF CORRESPONDENCE ADDRESS

As a below named inventor, I hereby declare that my residence, post office address and citizenship are as stated below next to my name, and that I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

METHOD FOR POWER LEVEL CONTROL OF A DISPLAY DEVICE AND APPARATUS FOR CARRYING OUT THE METHOD

the specification of which

(CHECK ONE) () is attached hereto.

(xx) was filed on July 31, 2000, Application Serial. No. PCT/EP 00/07395 and was amended on .

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with 37 CFR 1.56(a).

I hereby claim foreign priority benefits under 35 USC 119 of any foreign application(s) for patent, utility model, design or inventor's certificate having a filing date before that of the application(s) on which priority is claimed:

Prior Foreign Application(s)			Priority Claimed	
Number	Country	Date Filed	Yes	No
99250347.4	EP	September 30, 1999	xx	

I hereby claim the benefit under 35 USC 120 of any US Application(s) listed below, and, insofar as the subject matter of each of the claims of this Application is not disclosed in the prior US application in the manner provided by the first paragraph of 35 USC 112, I acknowledge the duty to disclose information which is material to the examination of this application in accordance with 37 CFR 1.56(a).

Serial No.: Filed:

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that wilful false statements and the like so made are punishable by fine or imprisonment, or both, under of 18 USC 1001 and that such wilful false statements may jeopardize the validity of the application or any patent issued thereon.

I hereby appoint the following attorneys to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith: Joseph S. Tripoli (Reg. No. 26,040) Telephone: (609) 734-9443.

Address all correspondence to Joseph S. Tripoli, Patent Operations - Thomson multimedia Licensing, Inc. - CN 5312 - Princeton, New Jersey 08543-0028.

Signature: [Signature] Date: 22 day of January, 2002.

Sole or First Joint Inventor: Carlos Correa

Citizenship: PT

Residence and Post Office Address:

Lichtenberger Weg 4
D-78056 Villingen-Schwenningen
Germany DEX

Signature: [Signature] Date: 22 day of January, 2002.

Second Joint Inventor: Sébastien Weitbruch

Citizenship: FR

Residence and Post Office Address:

Chabeuilstr. 17
D-78087 Mönchweiler
Germany DEX

Signature: *Rainer Zwing* Date: 24 day of January, 2002.

Third Joint Inventor: Rainer Zwing

Citizenship: DE

Residence and Post Office Address:

Bozener Str. 2

D-78052 Villingen-Schwenningen

Germany DEX

3-00